

Screwed Pipe Fittings - Grade 316

150lb Working Pressure, with British Standard Pipe Thread to BS21

(mm) DIAMETER (in)	
6.0	1/8"
8.0	1/4"
10.0	3/8"
15.0	1/2"
20.0	3/4"
25.0	1"
32.0	1 1/4"
40.0	1 1/2"
50.0	2"
65.0	2 1/2"
80.0	3"
100.0	4"

Socket



DIMENSIONS (mm)				DIMENSIONS (in)		
15.0	X	8.0	1/2"	X	1/4"	
15.0	X	10.0	1/2"	X	3/8"	
20.0	X	10.0	3/4"	X	3/8"	
20.0	X	15.0	3/4"	X	1/2"	
25.0	X	15.0	1"	X	1/2"	
25.0	X	20.0	1"	X	3/4"	
32.0	X	25.0	1 1/4"	X	1"	
40.0	X	25.0	1 1/2"	X	1"	
50.0	X	15.0	2"	X	1/2"	
50.0	X	25.0	2"	X	1"	
50.0	X	32.0	2"	X	1 1/4"	
50.0	X	40.0	2"	X	1 1/2"	

Reducing Socket



(mm) DIAMETER (in)	
6.0	1/8"
8.0	1/4"
10.0	3/8"
15.0	1/2"
20.0	3/4"
25.0	1"
32.0	1 1/4"
40.0	1 1/2"
50.0	2"
65.0	2 1/2"
80.0	3"
100.0	4"

Barrel Nipple

